



CUSHMAN®

TUG™



THE SUPREME TOWING MACHINE.

If you need a vehicle with exceptional towing capability, look no further than the Cushman® Tug.™ It's built to pull the heaviest loads, with your choice of 5,000-lb or 8,000-lb towing capacities. The Tug's silent, zero-emissions 36V DC drivetrain, three-wheel hydraulic brakes and simple, ergonomic controls make it an ideal choice for factories, distribution centers and other facilities. No matter the load, you can count on the Tug to pull its weight.

LET'S WORK.®

**UP TO
8000^{LB}**
TOWING CAPACITY

36V
ELECTRIC
DRIVETRAIN

4.9^{SQ FT}
CARGO DECK
CAPACITY



CUSHMAN® TUG™



VERSATILE TOWING CONNECTION



4.9-SQ-FT CARGO DECK

ERGONOMIC
BUCKET SEATING

OPTIONS & ACCESSORIES

- Steering Wheel
- Headlight
- Foam Filled Tires
- Lift-out Battery Tray
- Portable Charger
- Heavy-duty Battery Upgrade
- Certification Module E & EE
- CE Certification
- Hour Meter
- Clevis or Pintle Hitch
- Front Hydraulic Brake
- Solid Non-marking Tires



COVERED WITH THE 2-YEAR CUSHMAN
CARE TOTAL PROTECTION WARRANTY

5K MODEL

8K MODEL

BODY & CHASSIS		
FRAME	Welded Steel w/ DuraShield™ Powder Coat	
BODY & FINISH	4-way Embossed Diamond Pattern	
STANDARD COLOR	Safety Yellow	
DIMENSIONS		
OVERALL LENGTH	76.0 in (193 cm)	
OVERALL WIDTH	34.5 in (88 cm)	
OVERALL HEIGHT	37.0 in (94 cm)	
WHEEL BASE	52.5 in (133 cm)	
WHEEL TRACK	37.0 in (94 cm) Front / 29.7 in (75 cm) Rear	N/A Front / 29.7 in (75 cm) Rear
CARGO DECK MATERIAL	Heavy Duty Plywood	
POWER		
POWER SOURCE	36V DC SepEx	
HORSEPOWER (KW)	11.1 hp (8.28 kW) @ 1942 rpm	
ELECTRICAL SYSTEM	36V DC	
BATTERY (QTY/TYPE)	Six, 6V Deep Cycle	
BATTERY CHARGER	36V DC On-Board	
KEY OR PEDAL START	Pedal	
SPEED CONTROLLER	300 Amp Programmable. SRO Capable	
DRIVE TRAIN	Triple 'V' Belt	
GEAR SELECTION	Dash Mounted	
REAR AXLE RATIO	22.98:1	29.88:1
PERFORMANCE		
SEATING CAPACITY	1-Person	
WEIGHT W/O BATTERIES	571 lb (259 kg)	
CURB WEIGHT	940 lb (426 kg)	
VEHICLE LOAD CAPACITY	650 lbs (295 kg)	
TOWING CAPACITY	5000 lb (2267 kg)	8000 lb (3629 kg)
OUTSIDE CLEARANCE CIRCLE	9.0 ft (2.7 m)	
SPEED	Up to 7.8 mph (12.6 kmh)	Up to 6.0 mph (9.6 kmh)
STEERING & SUSPENSION		
STEERING	Handlebar	
SUSPENSION	Torsion Block (Front) / Coil Springs & Hydraulic Shock Absorber (Rear)	
SERVICE BRAKE	2-Wheel Hydraulic Drum	
PARKING BRAKE	Hand Lever, Mechanical Rear Brakes	
TIRES (FRONT & REAR)	USA Trail 4.80 x 8 (Load Range B)	

www.cushman.com

©2016 Textron Inc. All rights reserved. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

60014-G1 (Rev. 01/2016)