

SHUTTLE 2



DELIVERS MORE THAN HARD WORK.

When you need to move large materials around your facility in a hurry, the Cushman® Shuttle™ 2 is the right choice. With a 1,200-pound cargo capacity and a 20.9-square-foot cargo deck, it can move anything from lumber to luggage. And whether it's equipped with a 48V DC electric drivetrain or a 13.5 hp Kawasaki® gas engine, the Shuttle 2 offers plenty of power to get the job done right.

LET'S WORK.®

13.5 HP KAWASAKI® GAS ENGINE OPTION 48 V ELECTRIC DRIVETRAIN OPTION

20.9 SQ FT CARGO DECK





SHUTTLE 2





OPTIONS & ACCESSORIES

- Drop Side Rails
- Locking Glove Box
- Rear View Mirror
- Windshield
- Canopy
- Front Disc Brakes
- Pin Stripes
- Body Color (Forest Green, White or Custom Options)
- Turn Signal with Four-Way Flashers
- Strobe Lights

- Beacon Light Kit
- Dome and Work Lights
- LED Headlights
- Hour Meter
- High Altitude Jetting
- Fuse Cab
- Steel Cab and Doors
- Defroster
- Wheel Covers Spoke and Chrome
- Limited Slip Differential



	ELECTRIC MODEL	GAS MODEL
BODY & CHASSIS		
FRAME	Welded Steel w/ DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO (Front) / Steel Base Coat/Clear Coat (Rear)	
STANDARD COLOR	Patriot Blue	
DIMENSIONS	1/2 20 - 20 - 20 - 20 - 20 - 20 - 20 - 20	The state of the state of the state of
OVERALL LENGTH	141.0 in (358 cm)	
OVERALL WIDTH	48.5 in (123 cm)	
OVERALL HEIGHT	48.6 in (123 cm) (w/o Roof) / 72.0 in (183 cm) (w/ Struts & Roof)	
WHEEL BASE	93.5 in (237 cm)	
WHEEL TRACK	34.2 in (87 cm) Front / 38.0 in (97 cm) Rear	
GROUND CLEARANCE	4.3 in (11 cm)	4.75 in (12 cm)
CARGO DECK CAPACITY	20.9 sq ft (1.94 m²)	N/A
POWER		
POWER SOURCE	48V DC	4-Cycle, 24.5 ci (401cc) Low Emission
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	18.1 hp (13.5 kW) @ 1900 rpm	13.5 hp (10.1 kW) Exceeds SAE J1940 St
ELECTRICAL SYSTEM	48V	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPE)	Eight, 6V Deep Cycle	One, 12V Maintenance Free
BATTERY CHARGER	48 V, 120V AC, UL/CSA	N/A
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Industrial Rated Dry Filter
LUBRICATION	N/A	Pressurized Oil System
DIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	6 Gallon (22.7 L) Tank
SPEED CONTROLLER	400 Amp Precision Drive System (PDS)	N/A
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears Dash-Mounted Forward-Neutral-Reverse Forward - Reverse	
GEAR SELECTION		Forward - Reverse
REAR AXLE RATIO	14.7:1	11.42:1(Forward) 15.78:1(Reverse)
PERFORMANCE SEATING CAPACITY	2.0	overen
	2-Person	
WEIGHT W/O BATTERIES	810 lb (367 kg)	926 lb (420 kg)
CURB WEIGHT	1300 lb (590 kg)	N/A
VEHICLE LOAD CAPACITY	1000 lb (454 kg)	1200 lb (544 kg)
OUTSIDE CLEARANCE CIRCLE	25.5 ft (7.8 m)	N/A
SPEED	13 mph ± 0.5 mph (21 kph ± 0.8kph)	16 mph ± 0.5 mph (26 kph ± 0.8 kph)
STEERING & SUSPE		
STEERING	Self-Compensating Rack & Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum	
PARKING BRAKE	Self-Compensating, Single-Point Engagement	
TIRES (FRONT & REAR)	Links 18 x 8.5 - 8 (4 Ply Rated)	

www.cushman.com

©2016 Textron Specialized Vehicles Inc. All rights reserved. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.