

HAULER® PRO



FULLY LOADED AND READY TO WORK ALL DAY LONG.

Whether you are looking to move people or equipment, the Hauler® PRO gives you the flexibility to go farther and work longer. Powered by a quiet, zero emissions 72V AC electric drivetrain, the vehicle features a daily range of at least 50 miles, low vehicle maintenance, a 9.6-cubic foot cargo bed and a total capacity of 1,000 pounds. When you need the strong, silent type, look to the Cushman® Hauler PRO.

LET'S WORK®

72 V
AC ELECTRIC
DRIVETRAIN

1000 LB TOTAL LOAD CAPACITY 9.6 CU FT CARGO BED





FRAME **BODY & FINISH**

PARKING BRAKE

TIRES (FRONT & REAR)

CUSHMAN° HAULER® PRO

DuraShield™ Powder Coat

Injection Molded TPO (Front) / Steel Base Coat/Clear Coat (Rear)





OPTIC	INS 6	ACCE	SSORIES

- Limited Slip Differential
- · Locking Glove Box
- Windshield
- Roof
- Taillights · Brakelights
- Trailer Dump
- (Steel and Poly)
- 14.9 cu-ft Aluminum Cargo Bed
- Roll Over Protection System with Seat Belts and Side Nets
- 12 Volt Outlet

- Body Color (Patriot Blue, Ivory, White, Yellow, Orange or Custom Options)
- Turn Signal with Four-Way Flashers
- Strobe Lights
- Work Lights
- Weather Enclosure
- Defroster/Fan
- Steel Cab
- Beacon
- Hour Meter
- Ash Tray
- · Differential Guard
- Hydraulic Disc Brakes

STANDARD COLOR	Forest Green	
DIMENSIONS		
OVERALL LENGTH	111.0 in (282 cm)	
OVERALL WIDTH	49.8 in (126 cm)	
OVERALL HEIGHT	47.5 in (121 cm) (w/o Roof) / 70.8 in (180 cm) (w/ Struts & Roof)	
WHEEL BASE	75.3 in (191 cm)	
WHEEL TRACK	37.0 in (94 cm) Front / 38.0 in (97 cm) Rear	
GROUND CLEARANCE	5.5 in (14 cm)	
CARGO DECK CAPACITY	9.6 cu ft (0.27 m³)	
CARGO DECK MATERIAL	Roto-Molded Polyethylene	
POWER		
POWER SOURCE	72V DC	
HORSEPOWER (KW)	22.4HP (16.7 kW) - Measured at Peak Torque	
ELECTRICAL SYSTEM	72V	
BATTERY (QTY/TYPE)	Nine, 8V Deep Cycle	
BATTERY CHARGER	900 Watt 72V DC	
KEY OR PEDAL START	Pedal	
SPEED CONTROLLER	350 Amp AC	
DRIVE TRAIN	Motor Shaft Direct Drive	
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Seatwrap Mount Forward-Neutral-Reverse Switch	
REAR AXLE RATIO	17:01	
PERFORMANCE		
SEATING CAPACITY	2-Person (Bench)	
WEIGHT W/O BATTERIES	804 lb (365 kg)	
CURB WEIGHT	1371 lb (622 kg)	
VEHICLE LOAD CAPACITY	1000 lb (454 kg)	
BED LOAD CAPACITY	600 lb (272 kg)	
TOWING CAPACITY	1262 lb (572 kg) Max Load	
OUTSIDE CLEARANCE CIRCLE	22.1 ft (6.7 m)	
SPEED	13 mph \pm 0.5 mph (21 kph \pm 0.8 kph)	
STEERING & SUSPENSIO	ON	
STEERING	Self-Compensating Rack & Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum	



www.cushman.com

Self-Compensating, Single-Point Engagement

20 x 8 - 10 (4 Ply Rated) (Front) / 20 x 8 - 10 (4 Ply Rated) (Rear)